

NTN CR0-8807 tapered roller bearings

With over 10170 full-service stores, our NTN CR0-8807 tapered roller bearings inventory is extensive and our parts are priced right. 60 mm da within 24 hours. This 73.025 mm db helps you maximize your productivity by saving time and your hard-earned 57.15 mm dc dollars.

da	60 mm
db	73.025 mm
dc	57.15 mm
Da	130 mm
Ca	55.804 mm
A1	79.375 mm
A2	207.169 mm
S	4.763 mm
ba	38.1 mm
H	161.925 mm
H1	82.55 mm
H2	30.163 mm
J min.	219.075 mm
J max.	244.475 mm
J1	47.625 mm
L	285.75 mm
N1	15.875 mm
R1	49.212 mm
R2	19.05 mm
RG	1/8 NPT

PG	1/8 NPT
h	33.337 mm
Housing	FSAF 312
Bearing	22312 E
Lock nut	N 12
Lock washer	W 12
Stabilizing ring	SR-15-12
Taconite seal (db shaft position)	TER 47
Taconite seal (dc shaft position)	TER 33
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1075 r/min
P60°	42.3 kN
P90°	25.4 kN
P120°	15.6 kN
P150°	13.8 kN
P180°	16.9 kN
Pa	10.7 kN
Mass pillow block	14.1 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.5 in
Initial grease fill	87.885 g