## NTN DCL85 needle roller bearings

We work closely 0.0 Inventory with our NTN DCL85 needle roller bearings manufacturing partners N/A Minimum Buy Quantity to bring the best value to customers.

| Inventory                 | 0.0                                      |
|---------------------------|--|
| Manufacturer Name         | TIMKEN                                   |
| Minimum Buy Quantity      | N/A                                      |
| Weight                    | 34.958                                   |
| EAN                       | 0883450129954                            |
| Product Group             | M06288                                   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Tapered Adapter Sleeve                   |
| Housing Style             | 4 Bolt Pillow Block                      |
| Rolling Element           | Spherical Roller Bearing                 |
| Housing Material          | Cast Steel                               |
| Expansion / Non-expansion | Non-expansion                            |
| Mounting Bolts            | 3/4 Inch                                 |
| Relubricatable            | Yes                                      |
| Insert Part Number        | 22222                                    |
| Seals                     | Teflon Labyrinth                         |
| Housing Configuration     | 1 Piece Solid                            |
| Inch — Metric             | Metric                                   |
| Other Features            | Double Row   Extreme Duty   SAF<br>Style |

| Long Description                 | 4 Bolt Pillow Block; 100MM Bore;<br>125.41MM Base to Center Height;<br>Tapered Adapter Sleeve Mount;<br>Spher |
|----------------------------------|---|
| UNSPSC                           | 31171511  |
| Harmonized Tariff Code           | 8483.20.40.80   |
| Noun                             | Bearing   |
| Keyword String                   | Pillow Block  |
| Weight / LBS                     | 87  |
| Nominal Bolt Center to<br>Center | 13.2 Inch   335.3 Millimeter  |
| Actual Bolt Center to<br>Center  | 0 Inch   OMillimeter  |
| В                                | 4.937 Inch   125.41 Millimeter  |
| Bolt Spacing Minimum             | 11.875 Inch   301.625Millimeter   |
| d                                | 3.937 Inch   100 Millimeter   |
| Bolt Spacing Maximum             | 14.5 Inch   368.3Millimeter   |
| D                                | 4.13 Inch   104.902 Millimeter  |