

NTN DF08A15LLU/5C angular contact ball bearings

Our 230 mm Da highly-skilled and factory-trained service experts have the resources to help you with all your NTN DF08A15LLU/5C angular contact ball bearings needs – including routine maintenance, major repairs, warranty service, and 109.537 mm da 89.789 mm Ca equipment inspections.

da	109.537 mm
Da	230 mm
Ca	89.789 mm
A1	133.35 mm
A2	193.675 mm
S	4.763 mm
ba	65.881 mm
H	295.275 mm
H1	152.4 mm
H2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J1	82.55 mm
L	466.725 mm
N1	25.4 mm
R1	79.375 mm
R2	36.513 mm
RG	1/2 NPT
PG	1/4 NPT
h	60.325 mm

Housing	SAW 526
Bearing	23226 CCK/W33
Adapter sleeve assembly	SNW 126×4.5/16
Stabilizing ring	SR-26-0
Labyrinth ring	2 x LOR 115
End plug (suffix Y)	EPR 15
Bearing limiting speed	2600 r/min
P60°	189 kN
P90°	113 kN
P120°	73.8 kN
P150°	68.1 kN
P180°	84.5 kN
Pa	31.2 kN
Mass pillow block	68 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	3/8-16 UNC
Appropriate attachment bolt size G	0.875 in
Initial grease fill	382.73 g