

# NTN E - M275349D/M275310/M275310DG2 tapered roller bearings

NTN E-M275349D/M275310/M275310DG2 tapered roller bearings  
Manufacturers , Online Wholesale Suppliers ☐ Cast iron Housing  
material 50.8 mm d ! 111.6 mm Da

Housing material	Cast iron
d	50.8 mm
Da	111.6 mm
Db1	118 mm
Db2	127 mm
A	47 mm
A1	16 mm
A3	3.2 mm
A5	29.5 mm
B1	48.4 mm
B4	7.9 mm
J	184 mm
H	216 mm
L	127 mm
N	18 mm
s1	35.9 mm
T	66.9 mm
RG	1/4-28 UNF
R1	31.5 mm
Rα	45 °

DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	154 mm
J7	18 mm
N4	2 mm
Basic dynamic load rating C	43.6 kN
Basic static load rating C0	29 kN
Fatigue load limit Pu	1.25 kN
Limiting speed	3600 r/min
Thread grub screw G2	7/16-20 UNF
Hexagonal key size for grub screw N	5.556 mm
Recommended tightening torque for grub screw	28.5 N·m
Recommended diameter for attachment bolts, mm G	16 mm
Recommended diameter for attachment bolts, inch G	0.625 in
Housing	FYTB 511 M
Bearing	YET 211-200
End cover	ECY 211