

NTN EC0-CR-06B39STPX#08 tapered roller bearings

What 140x80x33 Size (mm) is the best 140 Bore Diameter (mm) place to buy NTN EC0-CR-06B39STPX#08 tapered roller bearings online? 80 Outer Diameter (mm) Manufacturing Service .

Size (mm)	140x80x33
Bore Diameter (mm)	140
Outer Diameter (mm)	80
Width (mm)	33
d	80 mm
D	140 mm
B	33 mm
d1	101 mm
D1	122.4 mm
F	95.3 mm
r1,2 – min.	2 mm
r3,4 – min.	2 mm
s	1.4 mm
da – min.	90 mm
da – max.	93 mm
db – min.	104 mm
Da – max.	129.8 mm
ra – max.	2 mm
Basic dynamic load rating – C	212 kN
Basic static load rating – C0	245 kN
Fatigue load limit – Pu	31 kN
Reference speed	5300 r/min

Limiting speed	8500 r/min
Calculation factor – kr	0.3
d1 ≈	101 mm
D1 ≈	122.4 mm
r1,2 min.	2 mm
r3,4 min.	2 mm
s max.	1.4 mm
da min.	90 mm
da max.	93 mm
db min.	104 mm
Da max.	129.8 mm
ra max.	2 mm
Basic dynamic load rating C	212 kN
Basic static load rating C0	245 kN
Fatigue load limit Pu	31 kN
Calculation factor kr	0.3
Limiting value e	0.3
Axial load factor Y	0.4
Mass bearing	2.2 kg
Angle ring	HJ 216 EC