

# NTN EE231462/232026D+A tapered roller bearings

Various types N/A Minimum Buy Quantity and sizes to accommodate your NTN EE231462/232026D+A tapered roller bearings requirements. 0.0 Inventory

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 25.878   |
| EAN                       | 0883450094276  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 7/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22220  |
| Seals                     | Triple Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   |
| Long Description          | 4 Bolt Pillow Block; 100MM Bore; 127MM Base to Center Height; Eccentric Collar Mount; Spherical Roll |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | QMPX20J100SEN                  |
| Weight / LBS                  | 67                             |
| D                             | 4.59 Inch   116.586 Millimeter |
| Bolt Spacing Maximum          | 14 Inch   355.6Millimeter      |
| d                             | 3.937 Inch   100 Millimeter    |
| B                             | 5 Inch   127 Millimeter        |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| Bolt Spacing Minimum          | 12.5 Inch   317.5Millimeter    |
| Nominal Bolt Center to Center | 13.3 Inch   336.8 Millimeter   |