

NTN FL673 deep groove ball bearings

Our highly-skilled and factory-trained service experts have the 9 Days Days to Ship resources Rubber Sealed Bearing Style to help you with all your NTN FL673 deep groove ball bearings needs – including routine maintenance, major repairs, warranty service, and equipment inspections.

| | |
|---------------------------------|---|
| Days to Ship | 9 Days |
| RoHS | 6 |
| Bearing Style | Rubber Sealed |
| Outer Ring Shape | [With Retaining Ring] With Retaining Ring Grooves |
| d | 10 |
| D | 30 |
| Width(mm) | 9 |
| Basic Dynamic Load Rating Cr(N) | 5100 |
| Basic Static Load Rating Cor(N) | 2390 |
| Shield Shape | Double Sealed/With Retaining Ring |
| Seal Material | Nitrile Rubber |
| Retaining Ring Size D2 max(mm) | 34.7 |
| f Maximum(mm) | 1.12 |
| h, Maximum(mm) | 3.18 |
| Type | Ball |
| Inner/Outer Ring Material | 440C Stainless Steel |
| Precision | Grade 0 |
| Features | Heat resistant / Anti-rust |
| Load Direction | Radial Load |

| | |
|-----------------------------|----------------------|
| Number of Raceway Ring Rows | Single Row |
| Size Standards | Metric System |
| The material of a ball | 440C Stainless Steel |
| Holder Material | 304 Stainless Steel |