

NTN GK28X35X18 needle roller bearings

What 25 mm d are the types of NTN GK28X35X18 needle roller bearings ? Manufacturing 12 mm B Service . Get Your Free, Instant price, design review.

d	25 mm
D	47 mm
B	12 mm
rs min	0.6 mm
Radial clearance class	CN
Mass	0.08 kg
Dynamic load, C	10.1 kN
Static load, C ₀	5.85 kN
Fatigue limit load, C _u	0.27 kN
f ₀	14.5
N _{lim} (grease)	9,400 rpm
Min operating temperature, T _{min}	-10 °C
Max operating temperature, T _{max}	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.49 Hz
Characteristic outer ring frequency, BPF ₀	4.12 Hz
Characteristic inner ring frequency, BRF ₀	5.88 Hz
da min	29 mm
da max	30.5 mm

Da max	43 mm
ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.079
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	25MM Bore; 47MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Polyacrylic Rubber Friction Seal Exxon Unirex Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.176

Outside Diameter	1.85 Inch 47 Millimeter
Outer Race Width	0.472 Inch 12 Millimeter
Bore	0.984 Inch 25 Millimeter
Inner Race Width	0 Inch 0 Millimeter