

# NTN GK41X46X21.8 needle roller bearings

NTN GK41X46X21.8 needle roller bearings Engineering Calculator , 15 Bore Diameter (mm) Manufacturing Service . Get 15x35x11 Size (mm) Your Free.

Size (mm)	15x35x11
Bore Diameter (mm)	15
Outer Diameter (mm)	35
Width (mm)	11
d	15 mm
D	35 mm
B	11 mm
C	11 mm
r min.	0,6 mm
da min.	19 mm
da max	20 mm
Da max.	31 mm
ra max.	0,6 mm
Weight	0,045 Kg
Basic dynamic load rating (C)	7,75 kN
Basic static load rating (C0)	3,6 kN
Reference speed	15 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.043
EAN	4547359004465

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6202LLU/3E
Weight / LBS	0.095
Bore	0.591 Inch   15 Millimeter
Outer Race Width	0.433 Inch   11 Millimeter
Outside Diameter	1.378 Inch   35 Millimeter
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania Prelubricat
Inner Race Width	0 Inch   0 Millimeter
bore diameter:	15 mm

precision rating:	ISO Class 0
outside diameter:	35 mm
finish/coating:	Uncoated
overall width:	11 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	11 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	11 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	15000 rpm
internal clearance:	CN
fillet radius:	0.6 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	23000 RPM
dynamic load capacity:	7750 N
series:	62
static load capacity:	3600 N
manufacturer product page:	<a href="#">Click here</a>