

NTN HKS8X12X9M needle roller bearings

What are the types of NTN HKS8X12X9M needle roller bearings ?
160.338 mm da Manufacturing 319.999 mm Da Service . Get Your Free, Instant price, design review.

| | |
|-------------------------------|----------------|
| da | 160.338 mm |
| Da | 319.999 mm |
| Ca | 95.809 mm |
| A1 | 180.975 mm |
| A2 | 254 mm |
| S | 4.763 mm |
| ba | 75.406 mm |
| H | 377.825 mm |
| H1 | 190.5 mm |
| H2 | 76.2 mm |
| L | 679.45 mm |
| R1 | 114.3 mm |
| R2 | 41.275 mm |
| RG | 3/4 NPT |
| PG | 1/4 NPT |
| h | 60.325 mm |
| Housing | SSAFS 536 |
| Bearing | 22236 CCK/W33 |
| Adapter sleeve assembly | SNW 36×6.5/16 |
| Stabilizing ring | SR-36-30 |
| Labyrinth ring | 2 x LOR 146 |
| PosiTrac Plus contact element | 2 x B10724-148 |

| | |
|--|----------------|
| End plug (suffix Y) | EPR 19 |
| Max. speed for PosiTrac Plus seal | 875 r/min |
| P60° | 535 kN |
| P90° | 320 kN |
| P120° | 196 kN |
| P150° | 173 kN |
| P180° | 202 kN |
| Pa | 46.3 kN |
| Mass pillow block | 197 kg |
| Cap bolt | 1-8 UNC |
| Cap bolt recommended tightening torque | 1220 N·m |
| Cap bolt, SAE grade | 8 |
| Eye bolt | 2 x 3/8-16 UNC |
| Initial grease fill | 1304.1 g |