

NTN HUB167-9 angular contact ball bearings

15 mm d are a few brands you will find in our inventory. Find NTN HUB167-9 angular contact ball bearings to see what's in stock!

| | |
|------------------------|----------|
| d | 15 mm |
| D | 35 mm |
| B | 11 mm |
| a min | 1.9 mm |
| a max | 2.06 mm |
| Ca min | 2.92 mm |
| Ca max | 3.18 mm |
| rs min | 0.6 mm |
| rNs min | 0.5 mm |
| D3 max | 33.17 mm |
| b min | 1.35 mm |
| b max | 1.65 mm |
| r0 max | 0.4 mm |
| D4 max | 39.7 mm |
| f | 1.12 mm |
| Snap ring reference | R35 |
| Radial clearance class | CM |
| Mass | 0.04 kg |
| Dynamic load, C | 7.75 kN |
| Static load, C0 | 3.6 kN |
| Fatigue limit load, Cu | 0.16 kN |
| f0 | 12.7 |

| | |
|---|-----------------|
| Nlim (grease) | 19,000 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.37 Hz |
| Characteristic rolling element frequency, BSF | 3.68 Hz |
| Characteristic outer ring frequency, BPF0 | 2.61 Hz |
| Characteristic inner ring frequency, BRFI | 4.39 Hz |
| da min | 19 mm |
| Da max | 31 mm |
| ra max | 0.6 mm |
| rNa max | 0.5 mm |
| Db min | 40.5 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.045 |
| Product Group | B00308 |
| Enclosure | 2 Metal Shields |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | Yes |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | Special |
| Inch – Metric | Metric |

| | |
|------------------------|--|
| Long Description | 15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO |
| Other Features | Deep Groove With Snap Ring Chevron SRI2 Prelubricated |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 0.099 |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outer Race Width | 0.433 Inch 11 Millimeter |
| Bore | 0.591 Inch 15 Millimeter |
| Outside Diameter | 1.378 Inch 35 Millimeter |