

NTN K12X17X7.8 needle roller bearings

NTN K12X17X7.8 needle roller bearings Warehouse offers car parts and 25x52x15 Size (mm) car accessories. 25 Bore Diameter (mm) We sell discount online as well 52 Outer Diameter (mm) as cheap machinery parts.

Size (mm)	25x52x15
Bore Diameter (mm)	25
Outer Diameter (mm)	52
Width (mm)	15
d	25 mm
D	52 mm
B	15 mm
C	15 mm
rn	0,5 mm
r min.	1 mm
da min.	30 mm
da max	32 mm
Da max.	47 mm
ra max.	1 mm
Weight	0,128 Kg
Basic dynamic load rating (C)	14 kN
Basic static load rating (C0)	7,85 kN
(Grease) Lubrication Speed	13 000 r/min
Inventory	2.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A

Weight / Kilogram	0.13
EAN	4547359004601
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	25MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6205ZZ
Weight / LBS	0.28
Outer Race Width	0.591 Inch 15 Millimeter
Bore	0.984 Inch 25 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	25 mm
static load capacity:	7850 N
outside diameter:	52 mm

precision rating:	ISO Class 0
overall width:	15 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Shielded
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	15 mm
snap ring included:	Without Snap Ring
outer ring width:	15 mm
internal clearance:	CN
maximum rpm (grease):	13000 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	1 mm
dynamic load capacity:	14000 N
manufacturer product page:	Click here