

# NTN K165×173×36 needle roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your NTN K165×173×36 needle roller bearings needs – including routine 0.0 Inventory maintenance, major repairs, warranty service, and equipment inspections.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 25.878   |
| EAN                       | 0883450027786                                  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar                              |
| Housing Style             | 4 Bolt Pillow Block                            |
| Rolling Element           | Spherical Roller Bearing                       |
| Housing Material          | Cast Steel                                     |
| Expansion / Non-expansion | Non-expansion                                  |
| Mounting Bolts            | 3/4 Inch                                       |
| Relubricatable            | Yes  |
| Insert Part Number        | 22220  |
| Seals                     | Teflon Labyrinth                               |
| Housing Configuration     | 1 Piece Solid                                  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Double Collar  <br>With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 4 Bolt Pillow Block; 3-15/16" Bore; 4-1/4" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QAAPF20A315ST  |
| Weight / LBS                  | 67   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| D                             | 5.94 Inch   150.876 Millimeter   |
| d                             | 3.938 Inch   100.025 Millimeter  |
| Nominal Bolt Center to Center | 12.5 Inch   317.5 Millimeter   |
| Bolt Spacing Minimum          | 10.875 Inch   276.225Millimeter  |
| B                             | 4.25 Inch   107.95 Millimeter  |
| Bolt Spacing Maximum          | 13.38 Inch   339.852Millimeter   |