

NTN K18×24×12 needle roller bearings

We work closely with our 2317 K Bearing (basic designation) NTN K18×24×12 needle roller bearings manufacturing partners to bring the best value H 2317 Adapter sleeve to customers.

| | |
|-----------------------------|----------------|
| Bearing (basic designation) | 2317 K |
| Adapter sleeve | H 2317 |
| Locating ring | 2 x FRB 5/180 |
| End cover | ASNH 520-617 R |
| Housing | SNL 520-617 RU |
| Oil seal | 2 x TSN 617 U |
| da | 75 mm |
| Ca | 70 mm |
| Da | 180 mm |
| A1 | 110 mm |
| A2 | 181 mm |
| H | 218 mm |
| H1 | 112 mm |
| H2 | 40 mm |
| J | 320 mm |
| L | 380 mm |
| N | 32 mm |
| N1 | 26 mm |
| J6 | 348 mm |
| J7 | 39 mm |
| N4 max. | 8 mm |
| P0° | 470 kN |

| | |
|---|----------|
| P55° | 620 kN |
| P90° | 370 kN |
| P120° | 280 kN |
| P150° | 250 kN |
| P180° | 310 kN |
| Pa | 200 kN |
| Q120° | 620 kN |
| Q150° | 360 kN |
| Q180° | 310 kN |
| Mass housing | 17.6 kg |
| Cap bolt, size | M 20×100 |
| Cap bolt, rec. tightening torque | 200 N·m |
| Appropriate attachment bolt, size G | 24 mm |
| Appropriate attachment bolt, rec. tightening torque | 665 N·m |
| Oil level, min. | 35 mm |
| Oil level, max. | 46 mm |