

NTN K30×38×18 needle roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your NTN K30×38×18 needle roller bearings needs 35 Bore Diameter (mm) – including routine maintenance, major repairs, warranty service, and 35x17x10 Size (mm) equipment inspections.

Size (mm)	35x17x10
Bore Diameter (mm)	35
Outer Diameter (mm)	17
Width (mm)	10
d	17 mm
D	35 mm
B	10 mm
d1	22.6 mm
d2	22.6 mm
D1	29.3 mm
K	0.5 mm
C1	6.05 mm
r1,2 – min.	0.3 mm
r3,4 – min.	0.2 mm
a	11.2 mm
da – min.	19 mm
db – min.	19 mm
Da – max.	33 mm
Db – max.	33.6 mm
ra – max.	0.3 mm

rb – max.	0.2 mm
dn	23.7 mm
Basic dynamic load rating – C	6.5 kN
Basic static load rating – C0	3.1 kN
Fatigue load limit – Pu	0.132 kN
Limiting speed for grease lubrication	45000 r/min
Limiting speed for oil lubrication	70000 mm/min
Ball – Dw	5.556 mm
Ball – z	12
Gref	0.54 cm ³
Calculation factor – e	0.68
Calculation factor – Y2	1.41
Calculation factor – Y0	0.76
Calculation factor – X2	0.67
Calculation factor – Y1	0.92
Preload class A – GA	40 N
Preload class B – GB	80 N
Preload class C – GC	160 N
Preload class D – GD	320 N
Calculation factor – f	1.04
Calculation factor – f1	0.99
Calculation factor – f2A	1
Calculation factor – f2B	1.02
Calculation factor – f2C	1.05
Calculation factor – f2D	1.08
Calculation factor – fHC	1
Preload class A	48 N/micron
Preload class B	62 N/micron
Preload class C	81 N/micron

Preload class D	107 N/micron
r _{1,2} min.	0.3 mm
r _{3,4} min.	0.2 mm
d _a min.	19 mm
d _b min.	19 mm
D _a max.	33 mm
D _b max.	33.6 mm
r _a max.	0.3 mm
r _b max.	0.2 mm
Basic dynamic load rating C	6.5 kN
Basic static load rating C ₀	3.1 kN
Fatigue load limit P _u	0.132 kN
Attainable speed for grease lubrication	45000 r/min
Attainable speed for oil-air lubrication	70000 r/min
Ball diameter D _w	5.556 mm
Number of balls z	12
Reference grease quantity G _{ref}	0.54 cm ³
Preload class A G _A	40 N
Static axial stiffness, preload class A	48 N/μm
Preload class B G _B	80 N
Static axial stiffness, preload class B	62 N/μm
Preload class C G _C	160 N
Static axial stiffness, preload class C	81 N/μm
Preload class D G _D	320 N
Static axial stiffness, preload class D	107 N/μm
Calculation factor f	1.04
Calculation factor f ₁	0.99
Calculation factor f _{2A}	1
Calculation factor f _{2B}	1.02

Calculation factor f2C	1.05
Calculation factor f2D	1.08
Calculation factor fHC	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y2	0.87
Calculation factor (single, tandem) Y0	0.38
Calculation factor (single, tandem) X2	0.41
Calculation factor (back-to-back, face-to-face) Y1	0.92
Calculation factor (back-to-back, face-to-face) Y2	1.41
Calculation factor (back-to-back, face-to-face) Y0	0.76
Calculation factor (back-to-back, face-to-face) X2	0.67
Mass bearing	0.038 kg