NTN KBK13X17X18.1 needle roller bearings

Advance 60 mm A NTN KBK13X17X18.1 needle roller bearings is your source for quality and 37.6 mm B accessories. shop online for home delivery or pick up in one of our 10000.

A1 30 mm B 37.6 mm B1 51.1 mm d 34.92 mm d1 51.1 mm G M6x1 H 95 mm H1 19 mm H2 140 mm J 127 mm L 167 mm L1 56 mm N 17mm NN 17mm NN 21 mm S1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min40 °C T max. 100 °C Weight	Α	60 mm
B 37.6 mm B1 51.1 mm d 34.92 mm d1 51.1 mm G M6x1 H 95 mm H1 19 mm H2 140 mm J 127 mm L 167 mm L1 167 mm NN 17mm NN 17mm NN 21 mm S1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min40 °C T max. 100 °C		
B1	A1	30 mm
d 34.92 mm d1 51.1 mm G M6x1 H 95 mm H1 19 mm H2 140 mm J 127 mm L 167 mm L1 56 mm N 17mm N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min. -40 °C T max. 100 °C	В	37.6 mm
d1 51.1 mm G M6x1 H 95 mm H1 19 mm H2 140 mm J 127 mm L 167 mm L1 56 mm N 17mm N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min. -40 °C T max. 100 °C	B1	51.1 mm
G M6x1 H 95 mm H1 19 mm H2 140 mm J 127 mm L 167 mm L1 56 mm N 17mm N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min. -40 °C T max. 190 °C	d	34.92 mm
H H1 H2 H2 H40 mm J 127 mm L 167 mm L1 167 mm N N 17mm N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min40 °C T max.	d1	51.1 mm
H1 19 mm H2 140 mm J 127 mm L 167 mm L1 56 mm N 17mm N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min40 °C T max. 100 °C	G	M6x1
H2 140 mm J 127 mm L 167 mm L1 56 mm N 17mm N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min40 °C T max. 100 °C	Н	95 mm
J 127 mm L 167 mm L1 56 mm N 17mm N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min. -40 °C T max. 100 °C	H1	19 mm
L 167 mm L1 56 mm N 17mm N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min. -40 °C T max. 100 °C	H2	140 mm
L1 56 mm N 17mm N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min. -40 °C T max. 100 °C	J	127 mm
N 17mm N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min. -40 °C T max. 100 °C	L	167 mm
N1 21 mm s1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min. -40 °C T max. 100 °C	L1	56 mm
\$1 36.3 mm S 18.8 mm C 25.7 kN C0 15.2 kN T min40 °C T max. 100 °C	N	17mm
S 18.8 mm C 25.7 kN C0 15.2 kN T min. -40 °C T max. 100 °C	N1	21 mm
C 25.7 kN C0 15.2 kN T min40 °C T max. 100 °C	s1	36.3 mm
C0	S	18.8 mm
T min40 °C T max. 100 °C	С	25.7 kN
T max. 100 °C	C0	15.2 kN
	T min.	-40 °C
Weight 2.41 kg	T max.	100 °C
	Weight	2.41 kg

Recommended tightening torque for set screw	8 Nm
Designation of housing	PH207-
Designation of bearing	EX207-22G2T04