

NTN KJ37X42X17 needle roller bearings

NTN KJ37X42X17 needle roller bearings, Units and Housings CAD models , Manufacturing Service . Get Your 64.795 mm Ca Free. 63.5 mm da

da	63.5 mm
Da	160 mm
Ca	64.795 mm
A1	98.425 mm
A2	149.225 mm
S	4.763 mm
ba	44.45 mm
H	192.088 mm
H1	101.6 mm
H2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
L	349.25 mm
N1	22.225 mm
R1	60.325 mm
R2	27.94 mm
RG	3/8 NPT
PG	1/8 NPT
h	40.481 mm
Housing	SAF 615
Bearing	22315 EK
Adapter sleeve assembly	SNW 115×2.1/2

Stabilizing ring	SR-18-15
Labyrinth ring	2 x LOR 38
PosiTrac Plus contact element	2 x B10724-37
End plug (suffix Y)	EPR 7
Max. speed for PosiTrac Plus seal	2350 r/min
P60°	121 kN
P90°	72.5 kN
P120°	45.4 kN
P150°	40.5 kN
P180°	49.8 kN
Pa	12.5 kN
Mass pillow block	24.3 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	141.75 g