

NTN KV38X44X19.8 needle roller bearings

are a few 35x60x65 Size (mm) brands you will find in our inventory. Find 35 Bore Diameter (mm) NTN KV38X44X19.8 needle roller bearings to see what's in stock!

Size (mm)	35x60x65
Bore Diameter (mm)	35
Outer Diameter (mm)	60
Width (mm)	65
da	35 mm
A	60 mm
B	65 mm
H	20 mm
H1	60 mm
H2	25 mm
J	170 mm
L	205 mm
N1	15 mm
J6	185 mm
J7	21 mm
N4 – max.	6 mm
A3	50 mm
A5	22 mm
ba – min.	34 mm
ba – max.	43 mm
Basic dynamic load rating – C	86.5 kN
Basic static load rating – C0	85 kN

Fatigue load limit – Pu	9.3 kN
Limiting speed	6500 r/min
Calculation factor – e	0.31
Calculation factor – Y1	2.2
Calculation factor – Y2	3.3
Diameter – dm	53.5 mm
Basic Designation bearing	22207 E
Pa	15 kN
P0°	150 kN
P55°	250 kN
P90°	150 kN
P120°	95 kN
P150°	85 kN
P180°	105 kN
Mass bearing unit	3.8 kg
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	3.81
EAN	7316574241866
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Stepped Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	12 Millimeter
Relubricatable	Yes

Insert Part Number	22207 E
Seals	Labyrinth
Housing Configuration	1 Piece Solid
Inch – Metric	Metric
Other Features	Double Row Locating Bearing With Grub Screw
Long Description	2 Bolt Pillow Block; 35MM Bore; 60MM Base to Center Height; Stepped Sleeve Mount; Spherical Roller B
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SYNT 35 FTS
Weight / LBS	8.38
Base to Center Height	2.362 Inch 60 Millimeter
Nominal Bolt Center to Center	6.7 Inch 170 Millimeter
Length Thru Bore	2.559 Inch 65 Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Actual Bolt Center to Center	6.7 Inch 170Millimeter
Bore	1.378 Inch 35 Millimeter
N	20 mm
ba min.	34 mm
ba max.	43 mm
N4 max.	6 mm
Basic dynamic load rating C	86.5 kN
Basic static load rating C0	85 kN
Fatigue load limit Pu	9.3 kN

Calculation factor e	0.31
Calculation factor Y1	2.2
Calculation factor Y2	3.3
Bearing mean diameter dm	53.5 mm
Basic bearing designation	22207 E
Attachment bolt diameter G	12 mm
Tightening torque for attachment bolts	80 N·m
Grub screws	3 x M 6
Tightening torque for grub screws	8 N·m
Grease quantity for relubrication	3 g
End cover	ECY 207