

NTN KV48X53X22.3 needle roller bearings

How do 180 mm Da you find the NTN KV48X53X22.3 needle roller bearings 107.95 mm da specification? Manufacturers Online Free check

da	107.95 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	228.6 mm
ba	46.831 mm
H	217.488 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J1	60.325 mm
L	387.35 mm
N1	22.225 mm
R1	58.737 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	39.688 mm
Housing	FSAF 024 KA
Bearing	23024 CCK/W33
Adapter sleeve assembly	SNW 3024×4.1/4

Stabilizing ring	2 x 38151-24
Taconite seal	TER 114
End plug (suffix Y)	EPR 14
Max. speed for Taconite seal	725 r/min
P60°	119 kN
P90°	71.2 kN
P120°	44.5 kN
P150°	40 kN
P180°	48.9 kN
Pa	16.7 kN
Mass pillow block	28.6 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g