## NTN KV61X66X31.8ZW needle roller bearings

Browse NTN KV61X66X31.8ZW needle roller bearings Categories in N/A Minimum Buy Quantity the Manufacturers TIMKEN Manufacturer Name Online Free. 0.0 Inventory including .

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 32.688   |
| EAN                       | 0883450085359  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22222  |
| Seals                     | Double Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Inch — Metric             | Inch   |
| Other Features            | Double Row   |
| Long Description          | 4 Bolt Pillow Block; 4-7/16" Bore; 4-3/4" Base to Center Height; Eccentric Collar Mount; S |

| UNSPSC                           | 31171511                        |
|----------------------------------|---------------------------------|
| Harmonized Tariff Code           | 8483.20.40.80                   |
| Noun                             | Bearing                         |
| Keyword String                   | Pillow Block                    |
| Weight / LBS                     | 82                              |
| Nominal Bolt Center to<br>Center | 13.2 Inch   335.3 Millimeter    |
| Actual Bolt Center to<br>Center  | 0 Inch   OMillimeter            |
| В                                | 4.75 Inch   120.65 Millimeter   |
| d                                | 4.438 Inch   112.725 Millimeter |
| D                                | 5.53 Inch   140.462 Millimeter  |
| Bolt Spacing Minimum             | 11.875 Inch   301.625Millimeter |
| Bolt Spacing Maximum             | 14.5 Inch   368.3Millimeter     |