

# NTN

## M275349D/M275310/M275310DG2 tapered roller bearings

NTN M275349D/M275310/M275310DG2 tapered roller bearings Industries and Applications ? 85 mm da We sell discount online as well as cheap machinery 80.963 mm dc parts.

da	85 mm
db	100.013 mm
dc	80.963 mm
Da	150 mm
Ca	45.796 mm
A1	88.9 mm
A2	127 mm
S	4.763 mm
ba	35.719 mm
H	187.325 mm
H1	95.25 mm
H2	38.1 mm
J min.	250.825 mm
J max.	279.4 mm
L	330.2 mm
N1	23.813 mm
R1	53.975 mm
R2	22.225 mm
RG	3/8 NPT
PG	1/8 NPT

h	34.925 mm
Housing	SAFS 217
Bearing	22217 E
Lock nut	AN 17
Lock washer	W 17
Stabilizing ring	SR-17-14
Labyrinth ring (db shaft position)	LOR 89
Labyrinth ring (dc shaft position)	LOR 63
End plug (suffix Y)	EPR 9
Bearing limiting speed	5600 r/min
P60°	78.7 kN
P90°	47.2 kN
P120°	28.9 kN
P150°	26.7 kN
P180°	32 kN
Pa	20.5 kN
Mass pillow block	23.1 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	218.29 g