

# NTN

## M667947D/M667911/M667911DG2 tapered roller bearings

How do I place an EMERGENCY order for a NTN M667947D/M667911/M667911DG2 tapered roller bearings that I want to pick up at a our store? 160x75x55 Size (mm)

Size (mm)	160x75x55
Bore Diameter (mm)	160
Outer Diameter (mm)	75
Width (mm)	55
d	75 mm
D	160 mm
B	55 mm
d1	103 mm
D1	132 mm
r1,2 – min.	2.1 mm
da – min.	87 mm
Da – max.	148 mm
ra – max.	2 mm
Basic dynamic load rating – C	156 kN
Basic static load rating – C0	143 kN
Fatigue load limit – Pu	5.5 kN
Reference speed	6700 r/min
Limiting speed	3600 r/min
Calculation factor minimum radial load – kr	0.06
Calculation factor – f0	14

d1 ≈	103 mm
D1 ≈	132 mm
r1,2 min.	2.1 mm
da min.	87 mm
Da max.	148 mm
ra max.	2 mm
Basic dynamic load rating C	156 kN
Basic static load rating C0	143 kN
Fatigue load limit Pu	5.5 kN
Calculation factor kr	0.06
Calculation factor f0	14
Mass bearing	4.8 kg