

NTN MR324120+MI-273220 needle roller bearings

Request A Quote For 40 Outer Diameter (mm) Your Special NTN MR324120+MI-273220 needle roller bearings 30 Bore Diameter (mm) Needs Today! Free 30x40x15 Size (mm) Quotes. ISO 9001 certified.

Size (mm)	30x40x15
Bore Diameter (mm)	30
Outer Diameter (mm)	40
Width (mm)	15
Fw	30 mm
D	40 mm
C	15 mm
Weight	0.044 Kg
Basic dynamic load rating (C)	17,1 kN
Basic static load rating (C0)	22,1 kN
(Grease) Lubrication Speed	5 500 r/min
Dw	3.5 mm
Lw	9.5 mm
Lubrication hole on outer ring	Non/No
Inner ring reference	IR25X30X16
Mass	0.04 kg
Cr	17.1 kN
C0r	22.1 kN
Nlim (grease)	5,500 rpm
Nlim (oil)	8,000 rpm
Min operating temperature, Tmin	-20 °C

Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.47 Hz
Characteristic outer ring frequency, BPF0	8.06 Hz
Characteristic inner ring frequency, BRFI	9.94 Hz
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.042
Product Group	B04144