

# NTN MR607632+MI-526032 needle roller bearings

NTN MR607632+MI-526032 needle roller bearings Needs Analysis , 22 Bore Diameter (mm) Manufacturing Service 22x10x6 Size (mm) . Get Your Free.

Size (mm)	22x10x6
Bore Diameter (mm)	22
Outer Diameter (mm)	10
Width (mm)	6
d	10 mm
D	22 mm
B	6 mm
d2	13.2 mm
D2	19.37 mm
r1,2 – min.	0.3 mm
da – min.	12 mm
da – max.	13 mm
Da – max.	20 mm
ra – max.	0.3 mm
Basic dynamic load rating – C	2.7 kN
Basic static load rating – C0	1.3 kN
Fatigue load limit – Pu	0.054 kN
Limiting speed	20000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	14
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	7316572207970
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Stainless Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	10MM Bore; 22MM Outside Diameter; 6MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No F
Other Features	Deep Groove   NBR Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	W 61900-2RS1
Weight / LBS	0.0207
Bore	0.394 Inch   10 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	0.866 Inch   22 Millimeter
Outer Race Width	0.236 Inch   6 Millimeter
d2 ≈	13.2 mm

D2 ≈	19.4 mm
r <sub>1,2</sub> min.	0.3 mm
d <sub>a</sub> min.	12 mm
d <sub>a</sub> max.	13 mm
D <sub>a</sub> max.	20 mm
r <sub>a</sub> max.	0.3 mm
Basic dynamic load rating C	2.34 kN
Basic static load rating C <sub>0</sub>	1.25 kN
Fatigue load limit P <sub>u</sub>	0.054 kN
Calculation factor k <sub>r</sub>	0.025
Calculation factor f <sub>0</sub>	14
Mass bearing	0.0093 kg