

# NTN NA4901L needle roller bearings

LET OUR NTN NA4901L needle roller bearings EXPERTS GET YOU THE PARTS N/A Minimum Buy Quantity YOU 0.0 Inventory NEED.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 8.626  |
| EAN                       | 0883450141130  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22213  |
| Seals                     | Teflon Labyrinth   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   |
| Long Description          | 2 Bolt Pillow Block; 65MM Bore; 76.2MM Base to Center Height; Eccentric Collar Mount; Spherical Roll |

|                               |                               |
|-------------------------------|-------------------------------|
| UNSPSC                        | 31171511                      |
| Harmonized Tariff Code        | 8483.20.40.80                 |
| Noun                          | Bearing                       |
| Keyword String                | Pillow Block                  |
| Manufacturer Item Number      | QMPXT13J065ST                 |
| Weight / LBS                  | 22                            |
| D                             | 3.37 Inch   85.598 Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter          |
| d                             | 2.559 Inch   65 Millimeter    |
| Bolt Spacing Maximum          | 8.78 Inch   223.012Millimeter |
| B                             | 3 Inch   76.2 Millimeter      |
| Nominal Bolt Center to Center | 8.2 Inch   208.3 Millimeter   |
| Bolt Spacing Minimum          | 7.66 Inch   194.564Millimeter |