

NTN NA0-50×68×20 needle roller bearings

NTN NA0-50×68×20 needle roller bearings Industries and Applications ? We sell discount 80 Outer Diameter (mm) online as well 40x80x23 Size (mm) as cheap machinery parts.

Size (mm)	40x80x23
Bore Diameter (mm)	40
Outer Diameter (mm)	80
Width (mm)	23
d	40 mm
Fw	49,5 mm
D	80 mm
B	23 mm
C	23 mm
r min.	1,1 mm
r1 min.	1,1 mm
Weight	0,743 Kg
Basic dynamic load rating (C)	72,5 kN
Basic static load rating (C0)	77,5 kN
(Grease) Lubrication Speed	7500 r/min
Enclosure	Open
Configuration	Single Row
Bore Type	Cylindrical Bore
Bore Size	40 mm
Outside Diameter	80 mm
Width	23 mm
Inside Ring Outside Diameter	49.5 mm

Fillet Radius/Chamfer	1.1 mm
r1	1.1 mm
Dynamic Load Rating	72,500 N
Static Load Rating	77,500 N
Limiting Speed – Grease	7,500 rpm
Limiting Speed – Oil	9,000 rpm
Radial Clearance	0.025 to 0.050 mm
db (min)	47 mm
db (max)	49 mm
dc (min)	52 mm
dd (min)	56 mm
Da (max)	73 mm
ra (max)	1 mm
ra1 (max)	1 mm