

NTN NF310 cylindrical roller bearings

170 Million used NTN NF310 cylindrical roller bearings instantly 0.0 Inventory searchable. Shop our large selection of parts based on brand, price, description, and location. Order the with SKF Manufacturer Name stock ...

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	5.72
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	20 Millimeter
Relubricatable	Yes
Insert Part Number	YAR 213-2RF
Seals	Multi Function Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Metric
Other Features	Single Row Standard Duty Wide Inner Race Y Bearing Has Flinger

Long Description	2 Bolt Pillow Block; 65MM Bore; 76.2MM Base to Center Height; Set Screw Mount; Ball Bearing; Relubri
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 65 TR
Weight / LBS	12.6
B	68.3 mm
Bolt Spacing Minimum	0 Inch 0Millimeter
Actual Bolt Center to Center	8 Inch 203Millimeter
d	65 mm
D	2.689 Inch 68.3 Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Nominal Bolt Center to Center	8 Inch 203 Millimeter
Housing material	Cast iron
A	65 mm
A1	44 mm
A5	35.5 mm
B4	10 mm
H	150 mm
H1	76.2 mm
H2	29 mm
J	203 mm
J max.	216 mm
J min.	190 mm
L	258 mm
N	35 mm

N1	22 mm
s1	42.9 mm
RG	1/4-28 UNF
R1	5.5 mm
R α	45 °
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	238 mm
J7	22.5 mm
N4	4 mm
Basic dynamic load rating C	57.2 kN
Basic static load rating C0	40 kN
Fatigue load limit Pu	1.7 kN
Limiting speed	1600 r/min
Mass bearing unit	5.35 kg
Thread grub screw G2	M10x1
Hexagonal key size for grub screw N	5 mm
Recommended tightening torque for grub screw	16.5 N·m
Recommended diameter for attachment bolts, mm G	20 mm
Recommended diameter for attachment bolts, inch G	0.75 in
Housing	SY 513 M
Bearing	YAR 213-2RF
End cover	ECY 213