

NTN NK110/40R+IR100×110×40 needle roller bearings

Our 170x130x5 Size (mm) highly-skilled and factory-trained service experts have the resources to help you with all your NTN NK110/40R+IR100×110×40 needle roller bearings needs 130 Outer Diameter (mm) – including routine maintenance, major repairs, warranty service, and 170 Bore Diameter (mm) equipment inspections.

Size (mm)	170x130x5
Bore Diameter (mm)	170
Outer Diameter (mm)	130
Width (mm)	5
d	130 mm
D	170 mm
Dw	5 mm
Ea – min.	136 mm
Eb – max.	167 mm
Basic dynamic load rating – C	112 kN
Basic static load rating – C0	830 kN
Fatigue load limit – Pu	93 kN
Reference speed	1100 r/min
Limiting speed	2200 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.252
EAN	7316577710383
Product Group	B04144

bore diameter:	130 mm
dynamic load capacity:	112 kN
outside diameter:	170 mm
cage material:	Steel
bearing width:	5 mm
maximum rpm:	2200 rpm
thrust bearing type:	Roller & Cage Assembly
compatible washer:	AS 130170, GS 81126, LS 130170, WS81126
operating temperature range:	Max +250 °F
series:	AXK
bearing material:	Steel
manufacturer product page:	Click here
static load capacity:	830 kN
manufacturer upc number:	7316577710383
Ea min.	136 mm
Eb max.	167 mm
Basic dynamic load rating C	112 kN
Basic static load rating C0	830 kN
Fatigue load limit Pu	93 kN
Mass roller and cage thrust assembly	0.2 kg
Universal washer	LS 130170
Thin universal washer	AS 130170
Shaft washer	WS 81126
Housing washer	GS 81126