

NTN NNU30/560C1NAP4 cylindrical roller bearings

NTN NNU30/560C1NAP4 cylindrical roller bearings Industries and 90 Outer Diameter (mm) Applications ? 55 Bore Diameter (mm) We sell discount 55x90x49.6 Size (mm) online as well as cheap machinery parts.

Size (mm)	55x90x49.6
Bore Diameter (mm)	55
Outer Diameter (mm)	90
Width (mm)	49,6
d	55 mm
d2	45 mm
D	90 mm
T	49,6 mm
T2	29,8 mm
d3	90 mm
r min.	1 mm
r1 min.	0,6 mm
A1	32,5 mm
B	10 mm
D1	57 mm
R	72 mm
Da max.	72 mm
ra max.	1 mm
rb max.	0,6 mm
Weight	1,22 Kg
Basic dynamic load rating (C)	70 kN

Basic static load rating (C0)	159 kN
(Grease) Lubrication Speed	2000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	1.44
EAN	0029176029660
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Double Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Double Row With Aligning Seat
Long Description	45MM Bore 1; 57MM Bore 2; 90MM Outside Diameter; 49.6MM Height; Ball Bearing; Double Direction; Not
Inch – Metric	Metric
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	54211
Weight / LBS	2.44713
Height	1.953 Inch 49.6 Millimeter
Bore 1	1.772 Inch 45 Millimeter

Outside Diameter	3.543 Inch 90 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 2	2.244 Inch 57 Millimeter
bore diameter:	45 mm
precision rating:	ABEC1, P0
outside diameter:	90 mm
static load capacity:	35500 lbf
overall width:	55 mm
dynamic load capacity:	15700 lbf
thrust bearing type:	Double-Direction
operating temperature range:	Maximum of +120 °C
outside diameter design:	Straight
maximum rpm:	3000 rpm
separable or banded:	Separable
cage material:	Steel Cage
race type:	Flat
series:	54200