

NTN NU326E cylindrical roller bearings

62 mm D offers a NTN NU326E cylindrical roller bearings selection of 25 mm d Genuine at Wholesale Prices. We are a NTN NU326E cylindrical roller bearings 17 mm B Certified Parts Retailer

d	25 mm
D	62 mm
B	17 mm
rs min	1.1 mm
Radial clearance class	C3
Mass	0.23 kg
Dynamic load, C	21.2 kN
Static load, C0	10.9 kN
Fatigue limit load, Cu	0.5 kN
f0	12.6
Nlim (oil)	14,000 rpm
Nlim (grease)	12,000 rpm
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.66 Hz
Characteristic outer ring frequency, BPF0	2.61 Hz
Characteristic inner ring frequency, BRFI	4.39 Hz
da min	31.5 mm
Da max	55.5 mm

ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.226
EAN	4547359386745
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	25MM Bore; 62MM Outside Diameter; 17MM Outer Race Diameter; 1 Metal Shield; Ball Bearing; ABEC 1 I
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6305ZC3
Weight / LBS	0.511
Bore	0.984 Inch 25 Millimeter
Outer Race Width	0.669 Inch 17 Millimeter

Outside Diameter	2.441 Inch 62 Millimeter
bore diameter:	25 mm
finish/coating:	Uncoated
outside diameter:	62 mm
bearing material:	High Carbon Chrome Steel
overall width:	17 mm
cage material:	Steel
bore type:	Round
inner ring width:	17 mm
closure type:	Single Shield
outer ring width:	17 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	12000 rpm
snap ring included:	Without Snap Ring
maximum rpm (oil):	14000 rpm
internal clearance:	C3
fillet radius:	1.1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	1400 RPM
dynamic load capacity:	21200 N
series:	63
static load capacity:	10900 N
manufacturer product page:	Click here
precision rating:	ISO Class 0