

# NTN R1031 cylindrical roller bearings

offers a NTN R1031 cylindrical roller bearings 0.0 Inventory selection of TIMKEN Manufacturer Name Genuine at Wholesale Prices. We are a NTN R1031 cylindrical roller bearings Certified Parts Retailer

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 9.988  |
| EAN                       | 0883450353021  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                                      |
| Housing Style             | 2 Bolt Pillow Block                                    |
| Rolling Element           | Spherical Roller Bearing                               |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22210  |
| Seals                     | Triple Lip Urethane                                    |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Collar   SN Style   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 2" Bore;<br>2-3/4" Base to Center Height;<br>Concentric Collar Mount; Spher |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QASN10A200SE0  |
| Weight / LBS                  | 28   |
| D                             | 2.87 Inch   72.898 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Bolt Spacing Minimum          | 7.2 Inch   182.88Millimeter  |
| B                             | 2.75 Inch   69.85 Millimeter   |
| Bolt Spacing Maximum          | 8.5 Inch   215.9Millimeter   |
| Nominal Bolt Center to Center | 7.9 Inch   199.5 Millimeter  |
| d                             | 2 Inch   50.8 Millimeter   |