

NTN RNA4918S needle roller bearings

With over 10170 full-service stores, our NTN RNA4918S needle roller bearings inventory is extensive and our parts are priced right. 60x130x46 Size (mm) within 24 60 Bore Diameter (mm) hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

Size (mm)	60x130x46
Bore Diameter (mm)	60
Outer Diameter (mm)	130
Width (mm)	46
d	60 mm
D	130 mm
B	46 mm
C	46 mm
r min.	2,1 mm
da min.	71 mm
Da max.	119 mm
ra max.	2 mm
Weight	2,57 Kg
Basic dynamic load rating (C)	88,5 kN
Basic static load rating (C0)	28,3 kN
(Grease) Lubrication Speed	4 300 r/min
(Oil) Lubrication Speed	5 300 r/min
Calculation factor (e)	0,4
Calculation factor (Y0)	1,6
Calculation factor (Y1)	1,6

rs min	2.1 mm
Associated sleeve reference	H2312X
e	0.4
Y1	1.6
Y2	2.4
Y0	1.6
Radial clearance class	CN
Precision class	P0
Mass	2.57 kg
Dynamic load, C	88.5 kN
Static load, C0	28.3 kN
Nlim (oil)	5,300 rpm
Nlim (grease)	4,300 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
da min	71 mm
da max	77 mm
db min	66 mm
Ce min	5 mm
Da max	119 mm
ra max	2 mm