

# NTN RNU6805 cylindrical roller bearings

100% Authentic. 28 Bore Diameter (mm) 15 Outer Diameter (mm)  
NTN RNU6805 cylindrical roller bearings Highest 28x15x20 Size  
(mm) Quality. Certified Supplier.

Size (mm)	28x15x20
Bore Diameter (mm)	28
Outer Diameter (mm)	15
Width (mm)	20
d	15 mm
D	28 mm
B	20 mm
C	18 mm
F	20 mm
r <sub>1,2</sub> – min.	0.3 mm
da – min.	17 mm
Da – max.	26 mm
ra – max.	0.3 mm
Basic dynamic load rating, radial direction – C	11.2 kN
Basic static load rating, radial direction – C <sub>0</sub>	15.3 kN
Basic dynamic load rating, axial direction – C	2.3 kN
Basic static load rating, axial direction – C <sub>0</sub>	2.4 kN
Fatigue load limit, radial direction – P <sub>u</sub>	1.8 kN

Fatigue load limit, axial direction – Pu	0.099 kN
Reference speed	19000 r/min
Limiting speed	22000 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.058
EAN	7316577015532
Product Group	B04144
bore diameter:	15 mm
closure type:	Open
outside diameter:	28 mm
fillet radius:	0.3 mm
overall width:	20 mm
lubrication type:	Grease
bearing type:	Needle Roller/Angular Contact Ball
cage material:	Steel
operating temperature range:	Max 250 °F
series:	NKIB
radial dynamic load capacity:	11.2 kN
manufacturer product page:	<a href="#">Click here</a>
radial static load capacity:	15.3 kN
manufacturer upc number:	7316577015532
bearing material:	Steel
weight:	0.11 lb
maximum rpm:	22000 rpm
r1,2 min.	0.3 mm

da min.	17 mm
Da max.	26 mm
ra max.	0.3 mm
Basic dynamic load rating, radial direction C	11.2 kN
Basic static load rating, radial direction C0	15.3 kN
Basic dynamic load rating, axial direction C	2.27 kN
Basic static load rating, axial direction C0	2.37 kN
Fatigue load limit, radial direction Pu	1.83 kN
Fatigue load limit, axial direction Pu	0.099 kN
Mass bearing	0.052 kg