

NTN SX0663LLUC4 deep groove ball bearings

What 50 mm d are the types of NTN SX0663LLUC4 deep groove ball bearings ? Manufacturing 90 mm D Service . Get Your Free, Instant price, design review.

d	50 mm
D	90 mm
B	20 mm
C	17 mm
T	21.75 mm
d1	69 mm
a	19.5 mm
rs min	1.5 mm
r1s min	1.5 mm
e	0.42
Y2	1.43
Y0	0.79
Mass	0.56 kg
ISO 355 reference	T3DB050
Dynamic load, C	77 kN
Rating life coefficient, A2	1
Static load, C0	93 kN
Fatigue limit load, Cu	11.3 kN
Nlim (oil)	5,300 rpm
Nlim (grease)	4,000 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C

Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.63 Hz
Characteristic outer ring frequency, BPF0	8.15 Hz
Characteristic inner ring frequency, BRFI	10.85 Hz
da max	58 mm
db min	58.5 mm
Da min	79 mm
Da max	81.5 mm
Db min	85 mm
Ca min	3 mm
Cb min	4.5 mm
ra max	1.5 mm
r1a max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.554
EAN	4547359291766
Product Group	B04334