

# PFI PHU2188 angular contact ball bearings

What 55 mm d is the best 120 mm D place to buy PFI PHU2188 angular contact ball bearings online? Manufacturing Service .

d	55 mm
D	120 mm
B	29 mm
rs min	2 mm
Radial clearance class	C3
Mass	1.37 kg
Dynamic load, C	71.5 kN
Static load, C0	45 kN
Fatigue limit load, Cu	2.05 kN
f0	13.2
Nlim (grease)	5,800 rpm
Min operating temperature, Tmin	-30 °C
Max operating temperature, Tmax	175 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.08 Hz
Characteristic outer ring frequency, BPF0	3.07 Hz
Characteristic inner ring frequency, BRFI	4.93 Hz
da min	64 mm
Da max	111 mm
ra max	2 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.344
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	55MM Bore; 120MM Outside Diameter; 29MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   IS
Other Features	Deep Groove   Chevron SRI2 Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	3.04237
Outside Diameter	4.724 Inch   120 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Bore	2.165 Inch   55 Millimeter
Outer Race Width	1.142 Inch   29 Millimeter