

# PFI PHU3193 angular contact ball bearings

PFI PHU3193 angular contact ball bearings Warehouse offers car parts and 125 Outer Diameter (mm) car accessories. We sell discount online as 80x125x29 Size (mm) well as cheap machinery parts.

Size (mm)	80x125x29
Bore Diameter (mm)	80
Outer Diameter (mm)	125
Width (mm)	29
d	80 mm
D	125 mm
T	29 mm
B	29 mm
C	22 mm
a	26,7 mm
r min.	1,5 mm
r2 min.	1,5 mm
da min.	88,5 mm
da max	89 mm
Da min	112 mm
Da max.	116,5 mm
Db min.	120 mm
ra max.	1,5 mm
rb max.	1,5 mm
Weight	1,32 Kg
Basic dynamic load rating (C)	147 kN

Basic static load rating (C0)	225 kN
(Grease) Lubrication Speed	2900 r/min
(Oil) Lubrication Speed	3900 r/min
Calculation factor (e)	0,42
Calculation factor (Y0)	0,78
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	1.32
EAN	0605790021237
Product Group	B04334
Precision Class	Standard
Component	Assembly
Basic Number	32016
Number of Tapered Rows	Single Row
Inch – Metric	Metric
Other Features	High Load Capacity
Long Description	Assembly; Standard Precision; 80MM Bore; 125MM Outside Diameter; 29MM Assembly Width; Single Row of
UNSPSC	31171516
Harmonized Tariff Code	8482.20.00.00
Noun	Bearing
Keyword String	Tapered
Manufacturer Item Number	32016JR
Weight / LBS	2.91
Outside Diameter	4.921 Inch   125 Millimeter
Bore	3.15 Inch   80 Millimeter
Assembly Width	1.142 Inch   29 Millimeter

Flange Outside Diameter	Ø Inch   Ø Millimeter
Bearing No.	32016JR
r(min)	1.5
r1(min)	1.5
Cr	185
CØr	225
Cu	34.6
Grease lub.	2900
Oil lub.	3900
a(mm)	26.7
da(min)	88.5
db(max)	89
Da(max)	116.5
Da(min)	112
Db(min)	120
Sa(min)	6
Sb(min)	7
ra(max)	1.5
rb(max)	1.5
e	0.42
Y1	1.42
YØ	0.78
(Refer.) Mass (kg)	1.32