

PSL PSL 412-301 cylindrical roller bearings

Browse PSL PSL 412-301 cylindrical roller bearings 0.0 Inventory Categories in the Manufacturers Online Free. including .

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.53
EAN	7316577049292
Product Group	B04286
Stud Profile	Male
Mounting Thread	M24 X 2
Thread Direction	Left Hand
Rolling Element	Spherical Plain
Material – Outer Member	Steel
Material – Ball	Steel
Material – Liner	Steel
Relubricatable	Yes
Enclosure	Open
Other Features	3 Piece Zinc Plated Outer
Long Description	25MM Bore; 18MM House Width; Male Stud Profile; M24 X 2; Left Hand Thread Direction; Spherical Plain
Inch – Metric	Metric
UNSPSC	31171508
Harmonized Tariff Code	8483.30.80.55

Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer Item Number	SAL 25 ES
Weight / LBS	1.168
Ball Width	0.787 Inch 20 Millimeter
d	25 mm
Housing Width	0.709 Inch 18 Millimeter
bore diameter:	25 mm
ball material:	Steel
misalignment angle:	7 °
race material:	Steel
shank thread length:	53 mm
radial static load capacity:	78 kN
rod end type:	Male Threaded
operating temperature range:	-30 to +130 °F
shank thread size:	M24x2
head diameter:	65 mm
thread direction:	Left Hand
head width:	18 mm
grade:	Commercial/Industrial
ball width:	20 mm
lubrication type:	With Lubrication Fitting
length to ball center:	94 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998
d2 max.	65 mm
B	20 mm
G	M 24x2

C1 max.	18 mm
h	94 mm
α	7 °
dk	35.5 mm
l1 min.	53 mm
l2 max.	128 mm
l7 min.	30 mm
r1 min.	0.6 mm
Basic dynamic load rating C	48 kN
Basic static load rating C0	78 kN
Specific dynamic load factor K	100 N/mm ²
Material constant KM	330
Mass rod end	0.53 kg