

PSL PSL 611-204 tapered roller bearings

Our 50x110x27 Size (mm) highly-skilled and factory-trained service experts have the resources to help 50 Bore Diameter (mm) you with all your PSL PSL 611-204 tapered roller bearings needs – including routine maintenance, major repairs, warranty service, and equipment inspections. 110 Outer Diameter (mm)

| | |
|--|-----------------------------------|
| Size (mm) | 50x110x27 |
| Bore Diameter (mm) | 50 |
| Outer Diameter (mm) | 110 |
| Width (mm) | 27 |
| Bearing Type | NUP |
| Bore Dia (d) | 50.0000 |
| Outer Dia (D) | 110.0000 |
| Width (B) | 27.0000 |
| Radius (min) (rs) | 2.000 |
| Dynamic Load Rating (Cr) | 110,000 |
| Static Load Rating (Cor) | 112,000 |
| Max Speed (Grease) (X1000 RPM) | 6 |
| Max Speed (Oil) (X1000 RPM) | 7 |
| Max. Shaft Shoulder Dia. Inner (Li) | 65.0 |
| Min. Housing Shoulder Dia., Outer (Lo) | 97.0 |
| Weight (g) | 1,209.00 |
| Precision | RBEC 1 |
| Standard Clearance | C0 |
| Material | 52100 Chrome steel, or equivalent |