

# PSL PSL 611-301 tapered roller bearings

100% N/A Minimum Buy Quantity Authentic. PSL PSL 611-301 tapered roller bearings 4.0 Inventory Highest Quality. Certified Supplier.

Inventory	4.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	6.65 lb
EAN	0087796060821
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Eccentric Collar
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	43/64 Inch
Relubricatable	Yes
Insert Part Number	G1115KPPB3
Seals	Double Triply
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 1-15/16" Bore; 6.2" Bolt Circle; 4-3/8" Bolt Spacing; 1 P

Other Features	Single Row   Normal Duty   With Set Screw
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	TCJ 1 15/16
Weight / LBS	6.65
Bolt Spacing	4.375 Inch   111.13 Millimeter
Cartridge Pilot Diameter	0 Inch   0 Millimeter
d	1.938 Inch   49.225 Millimeter
Nominal Bolt Circle Diameter Round	6.2 Inch   157 Millimeter
D	1.938 Inch   49.225 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter
Shaft Size d	1 15/16 in
Dimension D	4.437 in
Dimension E	2.614 in
Inside Ring Outside Diameter	2.728 in
Series	Industrial
Seal Type	Tri-Ply Seal
Total Length L	142.9 mm
Housing Width A	1.689 in
Bolt Hole Spacing J	111.1 mm
Bolt Hole Size N	16 mm
Flange Thickness A1	14.3 mm
Center of Bearing from Housing End A2	28.3 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm

Bolt Size	M16
Center of Bearing from Bearing End S	28.3 mm
Static Load Rating	5210 lbf
Dynamic Load Rating	8740 lbf