

PSL PSL 612-332 tapered roller bearings

100% Authentic. PSL PSL 612-332 tapered roller bearings 41.275×85.725×30.162 Size (mm) Highest Quality. Certified Supplier.

Size (mm)	41.275×85.725×30.162
Bore Diameter (mm)	41,275
Outer Diameter (mm)	85,725
Width (mm)	30,162
d	41,275 mm
D	85,725 mm
T	30,162 mm
B	30,162 mm
C	23,812 mm
ra1 max.	3,3 mm
a	21,8 mm
r min.	3,5 mm
r1 min.	3,3 mm
Da	73 mm
db	50 mm
ra max.	3,5 mm
da	57 mm
Db	81 mm
Weight	0,791 Kg
Basic dynamic load rating (C)	91 kN
Basic static load rating (C0)	115 kN
(Grease) Lubrication Speed	4300 r/min

(Oil) Lubrication Speed	6000 r/min
Calculation factor (e)	0,4
Calculation factor (Y0)	0,82
LangID	1
ALP23	0
outer r	3.3
ALP22	0
D_	85.725
ALP21	30
SHOG_yobi	3877R/3820R
RAr	152.135
inner r	3.5
GRS rpm	4300
D_b	81
D_a	73
DE_	73.169
SLR	21.3
Prod_Type3	TRBSR_ID_A
BETA_	2
ALPHA_	15
SDM_	63.654
DA1	10.618
DA2	9.138
hidYobi	3877/3820
Y1	1.5
B_	30.162
Oil rpm	6000
hidTable	ecat_NSTPRI
Y0	0.82

inner ra	3.5
outer rb	3.3
C0	115
CUP	0.285
e	0.4
DA_	9.882
BET21	4
BET22	0
BET23	0
Z_	16
C_	23.812
yobi	3877/3820
KBRG	3161
CONE	0.506
DI_	53.948