

Rotating Crane Truck Slew Bearing/Single-Row Ball Slewing Ring Wd-062.20.0844

What are the dimensions of a Rotating Crane Truck Slew Bearing/Single-Row Ball Slewing Ring Wd-062.20.0844? Manufacturing Service . 65x90x13 Size (mm) Get Your Free, Instant Quote

Size (mm)	65x90x13
Bore Diameter (mm)	65
Outer Diameter (mm)	90
Width (mm)	13
d	65 mm
D	90 mm
B	13 mm
C	13 mm
rn	0,5 mm
r min.	1 mm
da min.	70 mm
da max	71,5 mm
Da max.	85 mm
ra max.	1 mm
Weight	0,206 Kg
Basic dynamic load rating (C)	17,4 kN
Basic static load rating (C0)	16,1 kN
(Grease) Lubrication Speed	7 000 r/min
Inventory	0.0
Manufacturer Name	NTN

Minimum Buy Quantity	N/A
Weight / Kilogram	0.21
EAN	4547359006964
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	65MM Bore; 90MM Outside Diameter; 13MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6913ZZ/2AS
Weight / LBS	0.451
Outer Race Width	0.512 Inch 13 Millimeter
Bore	2.559 Inch 65 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
Other Features	Deep Groove Shell Alvania Prelubricated
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	65 mm

precision rating:	ISO Class 0
outside diameter:	90 mm
finish/coating:	Uncoated
overall width:	13 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	13 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	13 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	7000 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	8200 RPM
dynamic load capacity:	17400 N
series:	69
static load capacity:	16100 N
manufacturer product page:	Click here