

RUS2209 NTN C 23.000 mm 55x85x23mm Cylindrical roller bearings

| | |
|---|-----------|
| B | 23 mm |
| E | 75 mm |
| F | 55 mm |
| rs min | 1.1 mm |
| Radial clearance class | CN |
| Mass (without HJ ring) | 0.18 kg |
| Dynamic load, C | 61.5 kN |
| Static load, C0 | 68 kN |
| Fatigue limit load, Cu | 8.3 kN |
| Nlim (oil) | 9.000 rpm |
| Nlim (grease) | 7.600 rpm |
| Min operating temperature, Tmin | -40 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.42 Hz |
| Characteristic rolling element frequency, BSF | 6.35 Hz |
| Characteristic outer ring frequency, BPF0 | 5.92 Hz |
| Characteristic inner ring frequency, BRFI | 8.08 Hz |
| Da max | 78.5 mm |
| ra max | 1 mm |
| Bearing number | RUS2209 |
| Size (mm) | 55x85x23 |
| Brand | NTN |
| Bore Diameter (mm) | 55.000 |
| Outer Diameter (mm) | 85.000 |

| | |
|------------|-----------|
| Width (mm) | 23.000 |
| d | 55.000 mm |
| D | 85.000 mm |
| C | 23.000 mm |