

Ruville 5716 wheel bearings

Advance 160x65x37 Size (mm) Ruville 5716 wheel bearings is your source for quality and accessories. shop online 160 Bore Diameter (mm) for home delivery or pick up in one of our 10000 .

Size (mm)	160x65x37
Bore Diameter (mm)	160
Outer Diameter (mm)	65
Width (mm)	37
d	65 mm
D	160 mm
B	37 mm
D1	126.85 mm
F	89.3 mm
r1,2 – min.	2.1 mm
r3,4 – min.	2.1 mm
s	2.6 mm
da – min.	78 mm
da – max.	86 mm
db – min.	91 mm
Da – max.	146 mm
ra – max.	2 mm
rb – max.	2 mm
Basic dynamic load rating – C	183 kN
Basic static load rating – C0	190 kN
Fatigue load limit – Pu	24 kN
Reference speed	4800 r/min
Limiting speed	5600 r/min

Calculation factor – kr	0.15
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	3.56
EAN	7316577012814
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	65MM Bore; Straight Bore Profile; 160MM Outside Diameter; 37MM Width; Steel Cage Matetrial; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NU 413

Weight / LBS	7.959
Width	1.457 Inch 37 Millimeter
Outside Diameter	6.299 Inch 160 Millimeter
Bore	2.559 Inch 65 Millimeter
D1 ≈	126.85 mm
r1,2 min.	2.1 mm
r3,4 min.	2.1 mm
s max.	2.6 mm
da min.	78 mm
da max.	86 mm
db min.	91 mm
Da max.	146 mm
ra max.	2 mm
rb max.	2 mm
Basic dynamic load rating C	183 kN
Basic static load rating C0	190 kN
Fatigue load limit Pu	24 kN
Calculation factor kr	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	3.56 kg
Angle ring	HJ 413