

# Ruville 6618 wheel bearings

Shop Ruville 6618 wheel bearings huge online discount inventory. and Import machinery parts 15x28x7 Size (mm) your car needs with Free Shipping and Free Extended 28 Outer Diameter (mm) Warranty.

Size (mm)	15x28x7
Bore Diameter (mm)	15
Outer Diameter (mm)	28
Width (mm)	7
d	15 mm
D	28 mm
B	7 mm
C	7 mm
d1	18,8 mm
r1 min.	0,3 mm
r2 min.	0,3 mm
D1	24,2 mm
D2	25,3 mm
da min.	17 mm
Da max.	26 mm
rc max.	0,3 mm
Weight	0,016 Kg
Basic dynamic load rating (C)	4,36 kN
Basic static load rating (C0)	2,24 kN
Fatigue load limit (Pu)	0,095
Reference speed	56000 r/min
Limiting speed	34000 r/min
Calculation factor (f0)	14

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.01
EAN	7316577094988
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	15MM Bore; 28MM Outside Diameter; 7MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No F
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	61902
Weight / LBS	0.03
Bore	0.591 Inch   15 Millimeter
Outer Race Width	0.276 Inch   7 Millimeter
Outside Diameter	1.102 Inch   28 Millimeter
bore diameter:	15 mm
static load capacity:	2.24 kN

outside diameter:	28 mm
precision rating:	Not Rated
overall width:	7 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	7 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
snap ring included:	Without Snap Ring
maximum rpm:	34000 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	4.36 kN
d1 ≈	18.8 mm
D2 ≈	0 mm
r1,2 min.	0.3 mm
ra max.	0.3 mm
Basic dynamic load rating C	4.36 kN
Basic static load rating C0	2.24 kN
Fatigue load limit Pu	0.095 kN
Calculation factor kr	0.02
Calculation factor f0	14.3
Mass bearing	0.016 kg