

# SCE66 - P INA

## 9.525×14.288×9.525mm Outside Diameter 0.563 Inch | 14.3 Millimeter Needle roller bearings

Category	Needle Non Thrust Roller Bearings
BDI Inventory	14.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.009
EAN	4012802605631
Product Group – BDI	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly with Outer Ring – No Inner Ring
Enclosure	1 Seal
Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	No
Inch – Metric	Inch
Relubricatable	No
Thrust Bearing	No

Long Description	3/8" Bore; 9/16" Outside Diameter; 3/8" Width; Needle Roller Bearing; Roller Assembly with Outer Ring – No Inner Ring; 1 Seal Enclosure; No Self Aligning; Yes Retainer; Single Row of Rollers; No Separable; No Closed EndNo Relubricatable
Other Features	2 Rib Outer Ring   Drawn Cup Bearing   Steel Cage
Category – BDI	Needle Non Thrust Roller Bearing
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer URL	<a href="http://www.ina.com">http://www.ina.com</a>
Manufacturer Item Number	SCE66P
Weight / LBS	0.011
Bore	0.375 Inch   9.525 Millimeter
Outside Diameter	0.563 Inch   14.3 Millimeter
Width	0.375 Inch   9.525 Millimeter
Bearing number	SCE66-P
Size (mm)	9.525×14.288×9.525
Brand	INA
Bore Diameter (mm)	9.525
Outer Diameter (mm)	14.288
Width (mm)	9.525
F <sub>w</sub>	3/8 inch
F <sub>w</sub>	9.525 mm
D	0.563 inch

D	14.288 mm
C	0.375 inch
C	9.525 mm
m	0.011 lbs / Weight
m	5 g / Weight
$C_r$	650 lbf / Dynamic load rating (radial)
$C_r$	2900 N / Dynamic load rating (radial)
$C_{0r}$	610 lbf / Static load rating (radial)
$C_{0r}$	2700 N / Static load rating (radial)
$n_G$	25000 1/min / Limiting speed
$n_B$	18700 1/min / Reference speed