SIGMA MR-28 needle roller bearings

SIGMA MR-28 needle roller bearings, Units and Housings CAD models , 0.0 Inventory Manufacturing Service . Get Your N/A Minimum Buy Quantity Free.

| Inventory | 0.0 |
|-------------------------|---|
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.274 |
| EAN | 7316571004976 |
| Product Group | B00152 |
| Mounting Method | Shaft |
| Enclosure | 2 Seals |
| Rolling Element | Ball Bearing |
| Cage Material | Polyamide |
| Precision Class | ABEC 1 ISO PO |
| Internal Clearance | C0-Medium |
| Number of Rows of Balls | Double Row |
| Other Features | Allowable Misalignment 2.5 Deg Lubricated |
| Long Description | 30MM Bore; Shaft Mount; 62MM Outside Diameter; 20MM Inner Race Width; 20MM Outer Race Width; 2 Seals |
| Inch — Metric | Metric |
| UNSPSC | 31171532 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |

| Keyword String | Self Aligning |
|------------------------------|--|
| d | 1.181 Inch 30 Millimeter |
| D | 2.441 Inch 62 Millimeter |
| Inner Race Width | 0.787 Inch 20 Millimeter |
| Outer Race Width | 0.787 Inch 20 Millimeter |
| bore diameter: | 30 mm |
| dynamic load capacity: | 3507 lbf |
| outside diameter: | 62 mm |
| static load capacity: | 1045 lbf |
| overall width: | 20 mm |
| bearing material: | Steel |
| bore type: | Straight |
| cage material: | Polyamide |
| closure type: | Double Sealed |
| finish/coating: | Uncoated |
| internal clearance: | C0 |
| maximum misalignment: | 2.5 ° |
| operating temperature range: | 0 °F to 185 °F |
| application: | Metal manufacturing, Paper mills, Steel mills—plate, slab, strip, blast furnace, Overhead cran |