

# SIGMA N 2309 cylindrical roller bearings

What are the dimensions of 0.0 Inventory a SIGMA N 2309 cylindrical roller bearings? Manufacturing Service . Get Your Free, Instant Quote N/A Minimum Buy Quantity

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 35.38   |
| EAN                       | 0793699056938   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Adapter Sleeve  |
| Housing Style             | 4 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 20 Millimeter   |
| Relubricatable            | Yes   |
| Insert Part Number        | 22220LBC3   |
| Seals                     | Multi Labyrinth   |
| Housing Configuration     | 2 Piece Split   |
| Inch – Metric             | Metric  |
| Other Features            | Double Row  |
| Long Description          | 4 Bolt Pillow Block; 90MM Bore; 114.3MM Base to Center Height; Adapter Sleeve Mount; Spherical Roller |

|                               |                               |
|-------------------------------|-------------------------------|
| UNSPSC                        | 31171511                      |
| Harmonized Tariff Code        | 8483.20.40.80                 |
| Noun                          | Bearing                       |
| Keyword String                | Pillow Block                  |
| Manufacturer Item Number      | PLB68M90FR                    |
| Manufacturer Internal Number  | 5805693                       |
| Weight / LBS                  | 67.902                        |
| B                             | 4.5 Inch   114.3 Millimeter   |
| Nominal Bolt Center to Center | 12.1 Inch   308.5 Millimeter  |
| D                             | 0 Inch   0 Millimeter         |
| Bolt Spacing Maximum          | 13.126 Inch   333.4Millimeter |
| d                             | 3.543 Inch   90 Millimeter    |
| Bolt Spacing Minimum          | 11.626 Inch   295.3Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter          |