

# Single-Row Ball Four-Point Contact Ball Slewing Bearing for Tower Crane

Single-Row Ball Four-Point Contact Ball Slewing Bearing for Tower Crane Warehouse offers car parts and car accessories. We sell 18 mm C discount online as well as cheap machinery parts. 35 mm D

D	35 mm
d1	16 mm
C	18 mm
F	19 mm
B	19.5 mm
B1	52 mm
B2	32.5 mm
G	M16X1.5
G1	17 mm
B3	8 mm
C1	0.8 mm
n	6 mm
a	3 mm
e	21 mm
R	500 mm
Dw	4 mm
Lw	6 mm
Maximum tightening torque	52 Nm
Bearing with/without cage	Sans
Radial clearance class	CN

Precision class	P0
Mass	0.16 kg
Cr	22.3 kN
C0r	25.7 kN
Track load capacity spherical outer ring	3.2 kN
Nlim (grease)	5,500 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.58 Hz
Characteristic outer ring frequency, BPF0	7.44 Hz
Characteristic inner ring frequency, BRFI	10.56 Hz
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.212
Product Group	B04120