

# Single-Row Four Point Angular Contact Slewing Ball Bearing External Gear 9e-1b60-3585-1387

offers 0.0 Inventory a Single-Row Four Point Angular Contact Slewing Ball Bearing External Gear 9e-1b60-3585-1387 selection of Genuine at Wholesale Prices. We are N/A Minimum Buy Quantity a Single-Row Four Point Angular Contact Slewing Ball Bearing External Gear 9e-1b60-3585-1387 Certified Parts Retailer

|                        |  |
|------------------------|--|
| Inventory              | 0.0                                    |
| Manufacturer Name      | TIMKEN                                 |
| Minimum Buy Quantity   | N/A                                    |
| Weight                 | 6.04                                   |
| EAN                    | 0053893337647                          |
| Product Group          | B04334                                 |
| Precision Class        | Standard                               |
| Component              | Assembly                               |
| Basic Number           | 56425                                  |
| Assembly Number        | 90069                                  |
| Assembly Components    | 56425 (2)   56650D (1)   X1S-56425 (1) |
| End Play               | 0.006                                  |
| Number of Tapered Rows | Double Row                             |
| Inch – Metric          | Inch                                   |
| Other Features         | 2 Single Cone   1 Double Cup           |

|                          |   |
|--------------------------|---|
| Long Description         | Assembly; Standard Precision; Components 56425 (2)   56650D (1)   X1S-56425 (1); 4-1/4" Bore; 6 |
| UNSPSC                   | 31171516  |
| Harmonized Tariff Code   | 8482.20.00.00   |
| Noun                     | Bearing   |
| Keyword String           | Tapered   |
| Manufacturer Item Number | 56425-90069   |
| Weight / LBS             | 13.31   |
| Flange Outside Diameter  | 0 Inch   0 Millimeter   |
| d                        | 4.25 Inch   107.95 Millimeter   |
| D                        | 6.5 Inch   165.1 Millimeter   |
| Assembly Width           | 3.25 Inch   82.55 Millimeter  |