

Single-Row Non Gear Four Point Slewing Bearing 9o-1b20-0289-0295-7

Find the 62 mm D discount Single-Row Non Gear Four Point Slewing Bearing 9o-1b20-0289-0295-7 online 26.16 mm d you need . We offer ... If you check out our large 20.64 mm B selection of Single-Row Non Gear Four Point Slewing Bearing 9o-1b20-0289-0295-7 once .

d	26.16 mm
D	62 mm
B	20.64 mm
C	14.29 mm
T	19.05 mm
d1	46 mm
a	13.05 mm
e	0.35
Y2	1.71
Y0	0.94
Mass	0.3 kg
Dynamic load, C	46.5 kN
Rating life coefficient, A2	1.9
Static load, C0	54 kN
Fatigue limit load, Cu	6.6 kN
Nlim (oil)	8,200 rpm
Nlim (grease)	6,100 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C

Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.19 Hz
Characteristic outer ring frequency, BPF0	7.2 Hz
Characteristic inner ring frequency, BRFI	9.8 Hz
ra max	0.8 mm
r1a max	1.3 mm